

# K-SPEC® CABLE TIES

Before you source cable ties or related nylon products, please make a correct choice due to different application purpose

The Cable Ties will be applied to:	Material	Function	Flam Class	Main Material Type	Application Temp.
General Purpose	Nylon 66 (PA66)	General	UL-94V2	Dupont 101F, Ascend 21 SPF(C)	-40°C~+85°C (-40°F~+185°F)

### How to choose the right cable tie

The most important characteristics of a cable tie are:

- the raw-material they are made of (chemicals, weather, and heat resistance, low temperature resistance, the flammability rating)
- the tensile strength they can stand
- the max diameter they can bundle
- the shape of the tie in case of particular applications

### Chemicals resistance

please ask for information about the chemical resistance, if you need to apply the cable ties into a special area

### UV (Weather resistance)

All polymers including the polyamides used for the production of cable ties are sensitive to UV radiation. The most common additive used for protecting polyamides from UV radiation is carbon powder commonly known as "carbon black".

Natural Cable Ties have low resistance to UV radiation, but natural color usually can reflect the sunlight, so it could be used for general purpose outdoor. But not suggested for outdoor application

Black Cable Ties are additivated with carbon black. They have improved weather and UV radiation resistance and are better suitable for outdoor applications, but this is not enough to protect the material from the damage due to the UV-radiation for a long time. For these needs the weather resistance cable ties could be used.

And if for a long term of outdoor use, and we strongly suggest you to choose Strong UV resistance (weather resistance) material and our strong UV resistance material, it has been tested by UL as an available long term outdoor application.

### Temperature resistance

Polymers are also sensitive to temperatures.

All the material type above mentioned (except for Dupont MT409 & Ascend 41(47)), application of polyamide 6.6 cable ties is possible -10°C (26°F), the polyamide becomes very brittle at temperatures below -40°C (-40°F). So for continuous use of low temperature, suggested with -10°C (26°F). But Dupont MT409 & Ascend 41(47) could be applied with -40°C(-40°F) for a long term. The polyamide which can resistant and be applied with a high temperature, please read the related characters, and application temperature from the above table.

### Flamability

The UL 94 test, the Standard for Safety of Flammability of Plastic Materials for Parts in Devices and Appliances testing. The classifications relate to materials commonly used in manufacturing enclosures, structural parts and insulators found in consumer electronic products (V-0, V-1, V-2, HB, from the highest level to the lowest)

### Some Instructions for new UL standard 62275, and for your right choose of a cable ties.

- **Loop tensile strength**  
Type 1 or 11 based,  
No individual value shall be less than 50 % of the loop tensile strength declared after After heat aging, After temperature cycling.  
Type 2 or 21 based,  
No individual value shall be less than 100 % of the loop tensile strength declared after After heat aging, After temperature cycling.
- **Minimum installation temperature and Operation temperature test**  
According to the new standard of UL62275, the minimum installation temperature, and operation temperature test should be made. Different factory they will declare different minimum installation temperature, and operation temperature as well. so new UL will show such information and to show the quality of the products, and the characters of the products.
- **Smoke and heat generation**  
AH-1: Suitable for use in air-handling spaces — 1 (plenums) (for Metallic component, like stainless steel cable ties)  
AH-2: Suitable for use in air-handling spaces — 2 (plenums) (for Non-metallic component and Composite component, like nylon cable ties, cable ties fixing, coated stainless steel cable ties)

Tensile Strength, max bundle diameter, and other characteristics are listed in each table.



# K-SPEC® CABLE TIES

## Standard Nylon Cable Ties (General Purpose)

- Material with Pure Nylon 6.6, UL 94V-2, Operation temp. -40°C~+85°C (-40°F ~+185°F)
- Suggested Installation temp. -10°C~+85°C (14°F~185°F)
- Products listed with:



**A**



**RoHS PAHs Reach**



	Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
M	E4180C	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4180M	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E4189C	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4189M	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E6180C	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6180M	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E6189C	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6189M	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E8180C	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8180M	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E8189C	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8189M	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E14180C	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100
	E14180M	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000
E14189C	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100	
E14189M	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000	
I	E5400C	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5400M	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E5409C	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5409M	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E8400C	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8400M	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E8409C	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8409M	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E11400C	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11400M	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E11409C	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11409M	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E14400C	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100
	E14400M	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000
E14409C	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100	
E14409M	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000	

**NEW  
NEW  
NEW  
NEW**

### K-Spec® Part No. Instructions:

**E20175**



Pack Qty	Code
50	L
100	C
500	D
1000	M

Colour	Code	Colour	Code
Natural	9	Blue*	6
White*	WH	Purple*	7
UVB Resistant Black	0	Gray*	8
Brown*	1	FL. Orange*	16
Red*	2	FL. Yellow*	17
Orange*	3	FL. Green*	18
Yellow*	4	FL. Blue*	20
Green*	5		

\* 100,000 Piece Minimum Order for Coloured Ties

# K-SPEC® CABLE TIES

## Standard Nylon Cable Ties (General Purpose)

**A**

	Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.	
S	E5500C	Black	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	100	NEW
	E5500M	Black	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	1000	NEW
	E5509C	Natural	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	100	NEW
	E5509M	Natural	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	1000	NEW
	E7500C	Black	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	100	
	E7500M	Black	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	1000	
	E7509C	Natural	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	100	
	E7509M	Natural	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	1000	
	E11500C	Black	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	100	
	E11500D	Black	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	500	
	E11509C	Natural	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	100	
	E11509D	Natural	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	500	
	E14500C	Black	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	100	
	E14500D	Black	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	500	
	E14509C	Natural	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	100	
	E14509D	Natural	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	500	
	E17500C	Black	4.8 [.189]	430 [17.0]	122.5 [4.82]	22 [50]	100	
	E17509C	Natural	4.8 [.189]	430 [17.0]	122.5 [4.82]	22 [50]	100	
	E24500C	Black	4.8 [.189]	610 [24.0]	179.9 [7.08]	22 [50]	100	NEW
	E24509C	Natural	4.8 [.189]	610 [24.0]	179.9 [7.08]	22 [50]	100	NEW
E36500C	Black	4.8 [.189]	920 [36.0]	278.6 [10.97]	22 [50]	100	NEW	
E36509C	Natural	4.8 [.189]	920 [36.0]	278.6 [10.97]	22 [50]	100	NEW	
HD	E81200C	Black	7.6 [.300]	220 [8.6]	57.2 [2.25]	55 [120]	100	
	E81209C	Natural	7.6 [.300]	220 [8.6]	57.2 [2.25]	55 [120]	100	
	E111200C	Black	7.6 [.300]	300 [11.8]	82.8 [3.25]	55 [120]	100	
	E111209C	Natural	7.6 [.300]	300 [11.8]	82.8 [3.25]	55 [120]	100	
	E141200C	Black	7.6 [.300]	380 [15.0]	108.0 [4.25]	55 [120]	100	
	E141209C	Natural	7.6 [.300]	380 [15.0]	108.0 [4.25]	55 [120]	100	
	E181200L	Black	7.6 [.300]	450 [18.0]	130.5 [5.13]	55 [120]	50	NEW
	E181209L	Natural	7.6 [.300]	450 [18.0]	130.5 [5.13]	55 [120]	50	NEW
	E201200L	Black	7.6 [.300]	540 [21.0]	159.0 [6.25]	55 [120]	50	NEW
	E201209L	Natural	7.6 [.300]	540 [21.0]	159.0 [6.25]	55 [120]	50	NEW
	E221200C	Black	7.6 [.300]	550 [21.6]	162.5 [6.39]	55 [120]	100	
	E221209C	Natural	7.6 [.300]	550 [21.6]	162.5 [6.39]	55 [120]	100	
	E241200L	Black	7.6 [.300]	610 [24.0]	181.5 [7.14]	55 [120]	50	NEW
	E241209L	Natural	7.6 [.300]	610 [24.0]	181.5 [7.14]	55 [120]	50	NEW
	E301200L	Black	7.6 [.300]	750 [29.5]	226.1 [8.90]	55 [120]	50	NEW
	E301209L	Natural	7.6 [.300]	750 [29.5]	226.1 [8.90]	55 [120]	50	NEW