

# General Purpose Clamps

## Strap-Type Wire and Cable Clamps

These simple to use, economical wire management devices provide support for cables, conduit, wire, wire bundles and hydraulic/pneumatic tubing. The inside edges of the clamps are smooth, to protect the cable or wire insulation.



### Applications:

- Electrical, electronic and Mechanical panels
- Machinery
- Light duty Hydraulic and Pneumatic equipment

### Features and specifications:

- **Cable range:** (O.D.): from 3.2mm (~1/8") to 36.5mm (~1½")
- Three adjustable mounting hole models also available
- **Colours:** Natural (white) or Black
- **Packaging:** 100 pieces
- **Mounting:** To apply, snap the clamp around the cable, wire, tube or conduit, then mount with a single screw, bolt or rivet (not supplied). Mounting hole diameter "A" for ranges from 4.6mm to 5.0mm (~0.18" to 0.20")
- **Material:** Flame retardant, low-halogen Polyamide 6 (Nylon) UL94V2
- **Operating Temperature:** Maximum +90°C

### Strap-Type Wire and Cable Clamps (Order by Part No.)

Part No. (white)	Part No. (black)	Model	Offset B	Width C	Length E	Thickness F	Maximum O.D. cable	
							mm	in
103.103	103.104	UC00	9.5	9.6	19.8	1.4	3.20	1/8"
103.105	-	UC05	10.5	9.6	19.8	1.4	4.80	3/16"
103.106	103.107	UC10	12.0	10.0	22.0	1.4	6.35	¼"
103.108	-	UC15	12.0	10.0	22.0	1.5	7.90	5/16"
103.110	103.111	UC20	12.5	12.0	24.0	1.5	9.50	3/8"
103.112	103.113	UC30	15.2	12.0	31.0	1.5	12.70	½"
103.116	-	UC40	18.2	12.0	34.3	1.5	15.80	5/8"
103.120	-	UC50	18.2	12.0	35.0	1.5	19.40	¾"
103.125	103.124*	UC60	22.0	12.0	43.0	1.8	25.40	1"
103.126	-	UC65	24.0	12.0	50.0	1.8	27.50	1-1/16"
103.132	-	UC70	26.2	12.0	46.2	1.8	31.80	1-1/4"
103.137	103.138*	UC90	30.0	12.0	50.0	1.8	36.70	1-1/2"
<b>Adjustable models:</b>							<b>Range mm</b>	<b>Range inches</b>
103.146	-	PC0406	-	13.0	-	1.6	4.8 - 6.4	3/16" - ¼"
103.149	-	PC0609	-	13.0	-	1.6	6.7 - 9.5	¼" - 3/8"
103.154	-	P0914	-	13.0	-	1.6	9.5 - 14.3	3/8" - 9/16"

Information subject to change without notice - All dimensions in mm except where indicated. \* Special order only

